



HIMOINSA

MODEL
HDW-460 T5
 INDUSTRIAL RANGE
 Standard soundproofing
 Powered by DOOSAN



- H1
- WATER-COOLED
- THREE PHASE
- 50 HZ
- NON COMPLYING 97/68/EC
- DIESEL

Generating Rates



SERVICE		PRP	ESP
Power	kVA	460	507
Power	kW	368	405
Rated Speed	r.p.m.	1.500	
Standard Voltage	V	400/230	
Available Voltages	V	230 - 230/132	
Rated at power factor	Cos Phi	0,8	

01

HIMOINSA Company with quality certification ISO 9001

HIMOINSA gensets are compliant with EC mark which includes the following directives:

- 2006/42/CE Machinery safety.
- 2014/30/UE Electromagnetic compatibility.
- 2014/35/UE electrical equipment designed for use within certain voltage limits
- 2000/14/EC Sound Power level. Noise emissions outdoor equipment. (amended by 2005/88/EC)
- EN 12100, EN 13857, EN 60204

Ambient conditions of reference according to ISO 8528-1:2018 normative: 1000 mbar, 25°C, 30% relative humidity.

Prime Power (PRP):

According to ISO 8528-1:2018, Prime power is the maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load when operated for an unlimited number of hours per year under the agreed operating conditions with the maintenance intervals and procedures being carried out as prescribed by the manufacturer. The permissible average power output (Ppp) over 24 h of operation shall not exceed 70 % of the PRP.

Emergency Standby Power (ESP):

According to ISO 8528-1:2018, Emergency standby power is the maximum power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage or under test conditions for up to 200 h of operation per year with the maintenance intervals and procedures being carried out as prescribed by the manufacturers. The permissible average power output over 24 h of operation shall not exceed 70 % of the ESP

G2 class load acceptance in accordance with ISO 8528-5:2013

HIMOINSA HEADQUARTERS:

Fábrica: Ctra. Murcia - San Javier, Km. 23,6 | 30730 SAN JAVIER (Murcia) Spain
Tel.+34 968 19 11 28 Fax +34 968 19 12 17 Fax +34 968 19 04 20 | info@himoinsa.com | www.himoinsa.com

Manufacture facilities:

SPAIN • FRANCE • INDIA • CHINA • USA • BRAZIL • ARGENTINA

Subsidiaries:

PORTUGAL | POLAND | GERMANY | UK | SINGAPORE | UAE | PANAMA | DOMINICAN REPUBLIC | ARGENTINA | ANGOLA | SOUTH AFRICA





Engine Specifications 1.500 r.p.m.

ENGINE		PRP	ESP
Rated Output	kW	392	433
Manufacturer		DOOSAN	
Model		DP158LCF	
Engine Type		4-stroke diesel	
Injection Type		Direct	
Aspiration Type		Turbocharged and after-cooled	
Number of cylinders and arrangement		8-V	
Bore and Stroke	mm	128 x 142	
Displacement	L	14,618	
Cooling System		Coolant	
Lube Oil Specifications		API CH4 SAE 15W40 or 10W40	
Compression Ratio		15:1	
Fuel Consumption ESP	l/h	110,9	
Fuel Consumption 100% PRP	l/h	99,6	
Fuel Consumption 75 % PRP	l/h	72,9	
Fuel Consumption 50 % PRP	l/h	48,9	
Fuel Consumption 25 % PRP	l/h	27,6	
Lube oil consumption with full load		0,5 % of fuel consumption	
Total oil capacity	L	22	
Total coolant capacity	L	79	
Heat dissipated by coolant	kW	196	
Governor	Type	Electrical	
Air Filter	Type	Dry	

Generator

Generator		
Manufacturer		STAMFORD
Poles	No.	4
Connection type (standard)		Star-series
Mounting type		S-1 14"
Insulation	Class	H class
Enclosure (according IEC-34-5)		IP23
Exciter system		Self-excited, brushless
Voltage regulator		A.V.R. (Electronic)
Bracket type		Single bearing
Coupling system		Flexible disc
Coating type		Standard (Vacuum impregnation)



Application Data

Exhaust System

Maximum exhaust temperature	°C	529
Exhaust Gas Flow	m ³ /min	88
Maximum allowed back pressure	kPa	5,9
Exhaust Flange Size (external diameter)	mm	160
Heat dissipated by exhaust pipe	kW	410

Necessary Amount Of Air

Intake air flow	m ³ /h	1806
Cooling Air Flow	m ³ /s	11,67
Alternator fan air flow	m ³ /s	1,035

Starting System


Starting power	kW	7
Starting power	CV	9,52
Recommended battery	Ah	200 x 2
Auxiliary Voltage	Vdc	24

Fuel System

Fuel Oil Specifications		Diesel
Maximum power suction pump	mm Hg	225
Maximum return feed pump	mm Hg	450
Fuel Tank	L	740
Other fuel tank capacities	L	2.090



— Dimensions



H1 <i>Weight and Dimensions</i>		
(L) Length	mm	4.500
(H) Height	mm	2.340
(W) Width	mm	1.800
Maximum shipping volume	m ³	18,95
(*) Weight with liquids in radiator and sump	kg	4.931
Fuel tank capacity	L	740
Autonomy	Hours	10
Sound pressure level	dB(A)@7m	78 ± 2,4
(*) (with standard accessories)		STANDARD VERSION (Steel tank)

Himoinsa has the right to modify any feature without prior notice.
 Weights and dimensions based on standard products. Illustrations may include optional equipment.
 Technical data described in this catalogue correspond to the available information at the moment of printing.
 Industrial design under patent.

Local Distributor



Dimensions of Other Available Versions

<i>Weight and Dimensions</i>		
(L) Length	mm	4.500
(H) Height	mm	2.740
(W) Width	mm	1.800
Maximum shipping volume	m ³	22,19
(*) Weight with liquids in radiator and sump	kg	5.542
Fuel tank capacity	L	2.090,0
Autonomy	Hours	29
Sound pressure level	dB(A)@7m	78 ± 2,4

(*) (with standard accessories)

HIGH CAPACITY VERSION (Steel tank)



MODEL
HDW-460 T5
 INDUSTRIAL RANGE
 Standard soundproofing
 Powered by DOOSAN

CONTROL PANEL MODEL

M5

Digital manual Auto-Start control panel and thermal magnetic protection (depending on current and voltage) and differential with CEM7. Digital control unit CEM7



AS5

Automatic panel WITHOUT transfer switch and WITHOUT mains control with CEM7 unit. (*) AS5 as optional with CEA7 unit. Automatic panel without transfer switch and WITH mains control.



CC2

Himoinsa Switching cabinet WITH display. Digital control unit CEC7





MODEL

HDW-460 T5

INDUSTRIAL RANGE


Standard soundproofing

Powered by DOOSAN

CONTROL PANEL MODEL


AS5 + CC2

Automatic panel WITH transfer switch and with mains control. The display will be on the genset and on the cabinet. Digital control unit CEM7+CEC7



AC5

Automatic mains failure control panel. Wall-mounted cabinet WITH transfer switch and thermal magnetic protection (depending on current and voltage). Digital control unit CEA7





Controller features (I)

- : Standard
- x : Not included
- : Optional

Generator Readings	CEM 7	CEA 7	CEC 7	CEM7 + CEC7
Voltage between phases	•	•	•	•
Voltage between neutral and phase	•	•	•	•
Current intensities	•	•	•	•
Frequency	•	•	•	•
Apparent power (Kva)	•	•	•	•
Active power (Kw)	•	•	•	•
Reactive power (kVAr)	•	•	•	•
Power factor	•	•	•	•
Mains Readings	CEM 7	CEA 7	CEC 7	CEM7 + CEC7
Voltage between phases	x	•	•	•
Voltage between phases and neutral	x	•	•	•
Current intensities	x	•	•	•
Frequency	x	•	•	•
Apparent power	x	•	x	x
Active power	x	•	x	x
Reactive power	x	•	x	x
Power factor	x	•	x	x
Engine Readings	CEM 7	CEA 7	CEC 7	CEM7 + CEC7
Coolant temperature	•	•	x	•
Oil pressure	•	•	x	•
Fuel level (%)	•	•	x	•
Battery voltage	•	•	x	•
R.P.M.	•	•	x	•
Battery charge alternator voltage	•	•	x	•
Engine Protections	CEM 7	CEA 7	CEC 7	CEM7 + CEC7
High water temperature	•	•	x	•
High water temperature by sensor	•	•	x	•
Low water temperature by sensor	•	•	x	•
Low oil pressure	•	•	x	•
Low oil pressure by sensor	•	•	x	•
Low water level	•	•	x	•
Unexpected shutdown	•	•	x	•



Controller features (II)

- : Standard
- x : Not included
- : Optional

Engine Protections	CEM 7	CEA 7	CEC 7	CEM7 + CEC7
Fuel storage	•	•	x	•
Fuel storage by sensor	•	•	x	•
Stop failure	•	•	x	•
Battery voltage failure	•	•	x	•
Battery charge alternator failure	•	•	x	•
Overspeed	•	•	x	•
Underspeed	•	•	x	•
Start failure	•	•	x	•
Emergency stop	•	•	•	•
Alternator Protections	CEM 7	CEA 7	CEC 7	CEM7 + CEC7
High frequency	•	•	•	•
Low frequency	•	•	•	•
High voltage	•	•	•	•
Low voltage	•	•	•	•
Short-circuit	•	•	x	•
Asymmetry between phases	•	•	•	•
Incorrect phase sequence	•	•	•	•
Inverse power	•	•	x	•
Overload	•	•	x	•
Genset signal drop	•	•	•	•
Counters	CEM 7	CEA 7	CEC 7	CEM7 + CEC7
Total hour counter	•	•	•	•
Partial hour counter	•	•	•	•
Kilowatt meter	•	•	•	•
Starts valid counters	•	•	•	•
Starts failure counters	•	•	•	•
Maintenance	•	•	•	•
Communications	CEM 7	CEA 7	CEC 7	CEM7 + CEC7
RS232	•	•	•	•
RS485	•	•	•	•
Modbus IP	•	•	•	•
Modbus	•	•	•	•



Controller features (III)

- : Standard
- x : Not included
- : Optional

Communications	CEM 7	CEA 7	CEC 7	CEM7 + CEC7
CCLAN	•	•	x	•
Software for PC	•	•	•	•
Analogue modem	•	•	•	•
GSM/GPRS modem	•	•	•	•
Remote screen	•	•	x	•
Tele signal	• (8 + 4)	• (8 + 4)	x	• (8 + 4)
J1939	•	•	x	•
Features	CEM 7	CEA 7	CEC 7	CEM7 + CEC7
Alarm history	• (10) / (opc. +100)	• (10) / (opc. +100)	• (10) / (opc. +100)	• (10) / (opc. +100)
External start	•	•	•	•
Start inhibition	•	•	•	•
Mains failure start	x	•	•	•
Start under normative EJP	•	•	x	•
Pre-heating engine control	•	•	x	•
Genset contactor activation	•	•	•	•
Mains & Genset contactor activation	x	•	•	•
Fuel transfer control	•	•	x	•
Engine temperature control	•	•	x	•
Manual override	•	•	x	•
Programmable alarms	•	•	x	•
Genset start function in test mode	•	•	•	•
Programmable outputs	•	•	x	•
Multilingual	•	•	•	•
Special Functions	CEM 7	CEA 7	CEC 7	CEM7 + CEC7
GPS Positioning	•	•	x	•
Synchronisation	•	•	x	•
Mains synchronization	•	•	x	•
Second Zero elimination	•	•	x	•
RAM7	•	•	x	•
Remote screen	•	•	x	•
Programming timer	•	•	x	•



Generator set features

Engine

- ▣ Diesel engine
- ▣ 4-stroke cycle
- ▣ Water-cooled
- ▣ 24V electrical system
- ▣ Water separator filter (no visible level)
- ▣ Dry air filter
- ▣ Radiator with blower fan
- ▣ HTW sender
- ▣ LOP sender
- ▣ Electronic governor
- ▣ Hot parts protection
- ▣ Moving parts protection
- Optional : ▣ Radiator water level sensor

Alternator

- ▣ Self-excited and self-regulated
- ▣ IP23 protection
- ▣ H class insulation

Electrical system

- ▣ Electric control and power panel with measurements devices and control unit (according to necessity and configuration)
- ▣ 4-pole thermal magnetic circuit breaker
- ▣ Adjustable earth leakage protection (time & sensitivity) standard in M5 and AS5, with thermal magnetic protection
- ▣ Battery charger (standard on gensets with automatic control panels)
- ▣ Heating resistor (standard on sets with automatic control panels)
- ▣ Battery charger alternator with ground connection
- ▣ Starter battery/ies installed (cables and bracket included)
- ▣ Ground connection electrical installation with connection ready for ground spike (not supplied)
- Optional : ▣ Battery isolator

Soundproofed version

- ▣ Steel chassis
- ▣ Anti-vibration shock absorbers



Generator set features

Soundproofed version

- ▣ Chassis with integrated fuel tank
 - ▣ Fuel level gauge
 - ▣ Emergency stop button
 - ▣ Bodywork made from high quality steel plate
 - ▣ High mechanical strength
 - ▣ Low level of noise emissions
 - ▣ Soundproofing provided by high-density volcanic rock wool
 - ▣ Epoxy polyester powder coating
 - ▣ Full access for maintenance (water, oil and filters, no need to remove the bonnet)
 - ▣ Reinforced lifting hooks for crane hoisting
 - ▣ Watertight chassis (acts as a double barrier against liquid retention)
 - ▣ Fuel tank drain plug
 - ▣ Chassis drain plug
 - ▣ Chassis ready for future mobile kit installation
 - ▣ Steel residential silencer -35db(A) attenuation.
 - ▣ Oil sump extraction kit
 - ▣ Versatility to assemble a high capacity chassis with a metallic fuel tank
 - ▣ IP Protection according to ISO 8528-13:2016
- Optional :
- ▣ 3 way valve for external fuel supply (available in 1/2" and 3/8" fittings)
 - ▣ Fuel transfer pump



HIMOINSA

MODEL
HDW-460 T5
INDUSTRIAL RANGE
Standard soundproofing
Powered by DOOSAN

PDF Summary

Created : 04/04/2019 09:12
Author : Himoinsa
Number of pages : 13
Report Type: Data Sheet - **Industrial range**
Generated by: HIMOINSA Engineering Dept.
Page 1. Genset data
Page 2. Engine Specifications. Generator Specifications.
Page 3. Installation Data
Page 4. Dimensions
Page 5. Dimensions of Other Available Versions
Page 6. Control Panel Model
Page 7. Control Panel Model
Page 8. Controller features (I)
Page 9. Controller features (II)
Page 10. Controller features (III)
Page 11. Generator Features & Options
Page 12. Generator Features & Options
Page 13. PDF Summary



13



Ctra. Murcia - San Javier, km. 23,6 | 30730 San Javier (Murcia) SPAIN | Tel.: +34 902 19 11 28 / +34 968 19 11 28
Fax: +34 968 19 12 17 | Export Fax +34 968 19 04 20 | E-mail: info@himoinsa.com | www.himoinsa.com

